



Carhaulers & Equipment



5" CHANNEL BUGGY HAULER (B5)

6" CHANNEL SUPER-WIDE (B6)

8" CHANNEL SUPER-WIDE (B8)

ANGLE PIPETOP (P7)

ANGLE PIPETOP (P8)

4" CHANNEL CARHAULER (C4)

5" CHANNEL CARHAULER (C5)

6" CHANNEL CUSTOM CARHAULER (CC)

8" CHANNEL CARHAULER (C8)

LIGHT DUTY DECKOVER 5" CHANNEL (L5)

MEDIUM DUTY DECKOVER 6" CHANNEL (L6)





5" Channel Buggy Hauler (B5)





102" x 20' (B5) Pictured

Standard Features

- 7,000 lb. G.V.W.R.
- 3.500 lb. x 2 G.A.W.R.
- 2" Ball Coupler
- Safety Chains
- I Side Wind Drop-Leg Jack (8,000 lb.)
- 2 Posi-lube Axles, Idler & Brake (3,500 lb.)
- 4 Leaf Double-eye Spring Suspension
- 4 NEW 15" White Spoke Wheels
- 4 NEW ST205/75R15 Radial Tires (1,820 lb.)
- Electric Breakaway Kit w/ Charger
- · Rubrail & Stake Pockets
- 9" High Drive Over DP Steel Fenders
- 5' Channel Ramps w/ Holder
- 5" Channel Frame & Tongue
- 3" Channel Crossmembers 24" on Center

- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- DOT Approved Flushmount LED Lights
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Coupler Options

BP 2" A-Frame *
BP 2 5/16" A-Frame
BP 2" Adjustable
BP 2 5/16" Adjustable
3" Pintle Eye - Channel-mount (14,000 lb.)

Axle Options

- (2) 3,500# One Electric / Spring *
- (2) 3,500# Electric / Spring
- (2) 5,200# One Electric / Spring
- (2) 5,200# Electric / Spring

Tail Options

Straight Deck w/ 5' Slide-in Ramps *
2' Dovetail w/ 5' Slide-in Ramps
2' Dovetail w/ 2 Fold-up Ramps
Straight Deck w/ 2 Fold-up Ramps
Straight Deck w 4' Fold-up Gate
2' Dovetail w/ 4' Heavy Duty Fold-up Gate
Straight Deck w/ Rear Slide-in Ramps

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
Regatta Blue Powdercoat
Tractor Green Powdercoat
White Powdercoat

Other Options

10k Jack (Bumper Pull)
Plate for Winch
12" oc Crossmembers
2 D-Rings
2" Pipetop Removable Siderails
Steel Floor
Spare Tire Mount
Spare Tire and Mount
16"oc Crossmembers

* denotes a standard feature

Weights

Length	Axles	Est. Base Weight
18'	2 - 3,500	2360 lbs / 1070 kg
20'	2 - 3,500	2500 lbs / 1134 kg



6" Channel Super-Wide (B6)





102"x 22'(B6) Pictured

Standard Features

- 14.000 lb, G,V,W,R.
- 7.000 lb. x 2 G.A.W.R.
- 2 5/16" Ball Adjustable Coupler
- Safety Chains
- I Drop Leg Jack (10,000 lb.)
- 2 Posi-lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- 4 235/80R16 Radial Tires (3,520 lb.)
- Electric Breakaway Kit w/ Charger
- 5' Channel Ramps w/ Holder
- Rear Trailer Support Jacks
- 6" Channel Frame & Tongue
- 3" Channel Crossmembers 16" on Center
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- Sealed Wire Harness w/ 7-Way RV Plug

- · Sand Blasted, Acid Washed, Powder Coated
- · 4.000 lbs Rated Drive-over fenders
- Rubrail w/Stake Pockets
- Expaned Metal Chain Tray
- •DOT Approved Flushmount Lifetime LED Lights



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) *
BP 2 5/16" Adjustable Rigid Mount (25,000 lb.)
GN 2 5/16" Round (30,000 lb.) w/Toolbox
GN Load-Leveling 2 5/16" Square (30,000 lb.) & Tbx
3" Pintle Eye - Channel-mount (20,000 lb.)
GN 2 5/16" Square (30,000 lb.) w/Toolbox
GN 2 5/16" Round (25,000 lb.) w/Toolbox
GN 2 5/16" Square (25,000 lb.) w/Toolbox
HD 2 5/16" Adjustable Channel Mount 3 Bolt Coupler

Axle Options

(2) 5,200# Electric / Spring

(2) 7,000# Electric / Spring *

(2) 7,000# Load Range G 14ply Tires Electric / Spring

Tail Options

Straight deck w/ 5' Slide-in Ramps *

2' Dovetail w/ 5' Slide-in Ramps

2' Dovetail w/ 5' Fold-up Ramps

Straight deck w/ 5' Fold-up Ramps 2' Dovetail w/ HD Fold-up Ramps

4' Dovetail w/ 5' Slide-in Ramps

4' Dovetail w/ 5' Fold-up Ramps

2' Dovetail w/ 3 5' Fold-up Ramps

Straight Deck w/ 4' Heavy Duty Fold-up Gate

2" Dovetail w/ 4' Heavy Duty Fold-up Gate

2' Dovetaill w/ Split Heavy Duty Gate

2' Dovetail w/ 5' Double Hinge Fold-up Ramps

2' Dovetail w/ 5' Rear Slide-in Ramps

4' Dovetail w/ 5' Rear Slide-in Ramps

Straight Deck w/ Rear Slide-in Ramps

Straight deck w/ HD Fold-up Ramps

4' Dovetaill w/ Split Heavy Duty Gate

4' Dovetail w/ HD Fold-up Ramps

4' Dovetail w/ 5' Double Hinge Fold-up Ramps Straight deck w/ 3 5' Fold-up Ramps

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
White Powdercoat

Other Options

Cold Weather Wiring Harness (7-Way RV)
2nd Jack (Bumper Pull)
Plate for Winch
6"Taller GN Riser
Douglas Fir Lumber
¼" Diamond Plate Steel Floor ²
9,990 G.V.W.R.
12"oc Crossmembers
1 Pair D-Rings
Rough Oak Floor
Receiver Hitch
Goodyear 14 Ply Tire MUST ADD TO REG 14 PLY COST
2 3/8" Removable Pipetop on Siderails
1 I ga Diamond Plate Steel Floor & 4 D-Rings

Front Toolbox (Bumper Pull)
Mount Only for Spare Tire
Spare Tire and Mount (Bumper Pull)
Deck on the Neck (GN Only)
Rear Trailer Support Jacks
Winch 12VDC (12,000 lb.) Incl. Front Toolbox
2-speed Jack (12,000 lb.)

* denotes a standard feature

Weights

Length	Axles	Est. Base Weight	
22'	2 - 7,000	3750 lbs / 1701 kg	



8" Channel Super-Wide (B8)





102" x 30' (B8) with Optional Spare Tire & Mount Pictured

Standard Features

- 14.000 lb, G,V,W,R.
- 7.000 lb. x 2 G.A.W.R.
- 2 5/16" Ball A-Frame Coupler
- Safety Chains
- I Drop Leg Jack (10,000 lb.)
- 2 Posi-lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- · 4 235/80R16 Radial Tires (3,520 lb.)
- Stake Pockets
- Electric Breakaway Kit w/ Charger
- 5' Channel Ramps w/ Holder
- Rear Trailer Support Stands
- Front Toolbox (GN Only)
- 8" Channel Frame & Tongue
- 3" Channel Crossmembers 16" on Center
- 102" Wide Rail to Rail

• 2" Treated Pine Lumber Deck

- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness w/ 7-Way RV Plug
- Sand Blasted, Acid Washed, Powder Coated
- Expanded Metal Chain Tray (Bumper Pull)



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight;	
24'	2 - 7,000	4680 lbs / 2123 kg	
24' GN	2 - 7,000	5280 lbs / 2395 kg	

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights



Triple Axle Hot-Shot Trailer

Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) * BP 2 5/16" Adjustable Rigid Mount (25,000 lb.) GN 2 5/16" Round (30,000 lb.) w/Toolbox GN Load-Leveling 2 5/16" Square (30,000 lb.) & Tbx 3" Pintle Eye - Channel-mount (20,000 lb.) GN 2 5/16" Square (30,000 lb.) w/Toolbox GN 2 5/16" Round (25,000 lb.) w/Toolbox GN 2 5/16" Square (25,000 lb.) w/Toolbox HD 2 5/16" Adjustable Channel Mount 3 Bolt Coupler

Axle Options

- (2) 7,000# Electric / Spring *
- (2) 7,000# Elec/Hyd Drum (1,000 PSI Pump) / Spring
- (2) 7,000# Elec/Hyd Disk (1,600 PSI Pump) / Spring
- (3) 7,000# Electric / Spring
- (3) 7,000# Elec/Hyd Disk (1,600 PSI Pump) / Spring
- (2) 7,000# Load Range G 14ply Tires Electric / Spring
- (2) 7,000# LR G 14ply Tires Elec/Hyd Drum (1,000 PSI)/Spring
- (2) 7,000# LR G 14ply Tires Elec/Hyd Disk (1,600 PSI)/Spring
- (3) 7,000# LR G 14ply Tires Electric / Spring
- (3) 7,000# LR G 14ply Tires Elec/Hyd Disk (1,600 PSI)/Spring

Tail Options

Straight deck w/ 5' Slide-in Ramps *

2' Dovetail w/ 5' Slide-in Ramps

2' Dovetail w/ 5' Fold-up Ramps

Straight deck w/ 5' Fold-up Ramps

2' Dovetail w/ HD Fold-up Ramps

4' Dovetail w/ 5' Slide-in Ramps 4' Dovetail w/ 5' Fold-up Ramps

2' Dovetail w/ 3 5' Fold-up Ramps

Straight Deck w/ 4' Heavy Duty Fold-up Gate

2" Dovetail w/ 4' Heavy Duty Fold-up Gate

2' Dovetaill w/ Split Heavy Duty Gate

2' Dovetail w/ 5' Dbl Hinge Fold-up Ramps

2' Dovetail w/ 5' Rear Slide-in Ramps

4' Dovetail w/ 5' Rear Slide-in Ramps Straight Deck w/ Rear Slide-in Ramps

Straight deck w/ HD Fold-up Ramps

4' Dovetaill w/ Split Heavy Duty Gate

4' Dovetail w/ HD Fold-up Ramps

4' Dovetail w/ 5' Dbl Hinge Fold-up Ramps

Straight deck w/ 3 5' Fold-up Ramps

Other Options

Cold Weather Wiring Harness (7-way RV) 2nd Jack (Bumper Pull)

Plate for Winch

6" Taller GN Riser

Douglas Fir Lumber

1/4" Diamond Plate Steel Floor 2

9,990 G.V.W.R.

12"oc Crossmembers

I Pair D-Rings

Rough Oak Floor

Hydraulic Jacks (12,000 lb.) Incl. Small Toolbox 2 Receiver Hitch

Goodyear 14 Ply Tire (add to 14ply axle option)

2 3/8" Removable Pipetop on Siderails

I I ga Diamond Plate Steel Floor & 4 D-Rings Front Toolbox (Bumper Pull)

Mount Only for Spare Tire

Spare Tire and Mount (Bumper Pull)

Deck on the Neck (GN Only)

Rear Trailer Support Jacks

Winch 12VDC (12,000 lb.) Incl. Front Toolbox 2-speed Jacks (12,000 lb.)

^{*} denotes a standard feature



Angle Pipetop (P7)





Standard Features

- 9.990 lb. G.V.W.R.
- 5,200 lb. x 2 G.A.W.R.
- 2 5/16" Ball Coupler
- Safety Chains
- I Jack (7,000 lb.)
- 2 Posi-lube Brake Axles (5,200 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 15" White Spoke Wheels
- 4 225/75R15 Radial Tires
- Electric Breakaway Kit w/ Charger
- 5' Channel Ramps w/ Holder
- 2x3 Angle Upright
- 2 7/8 Pipe Top Rail
- 5" Channel Tongue & 3" x 5" Angle Frame
- 2x3 Angle 24" on Center

- 2" Treated Pine Lumber Deck
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated
- DOT Approved Flushmount Lifetime LED Lights



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams M Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Coupler Options

BP 2 5/16" A-Frame *
BP 2 5/16" Adjustable

Axle Options

(2) 5,200# Electric / Spring *
(2) 5,200# One Electric / Spring

Tail Options

Straight deck w/ 5' Slide-in Ramps *
Straight deck w/ 5' Fold-up Ramps

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
White Powdercoat

Other Options

Upgrade to 3" X 3" Square Tubing Top Rail 2x3 Angle 16" on Center Upgrade I Pair D-Rings Receiver Hitch Spare Tire Mount Spare Tire and Mount

* denotes a standard feature



AIR RIDE SUSPENSION AVAILABLE

Weights

Length	Axles	Est. Base Weight
16'	2 - 5,200	2420 lbs / 1098 kg
18'	2 - 5,200	2590 lbs / 1175 kg
20'	2 - 5,200	2760 lbs / 1252 kg



Angle Pipetop (P8)



Coupler Options BP 2 5/16" Adjustable (14,000 lb.) * Rigid mount 2-5/16 (25,000 lb.) GN 2 5/16" Round (30,000 lb.) w/Toolbox GN Load-Leveling 2 5/16" Square (30,000 lb.) & Tbx 3" Pintle Eye - Channel-mount (21,000 lb.) GN 2 5/16" Square (30,000 lb.) w/Toolbox GN 2 5/16" Round (25,000 lb.) w/Toolbox GN 2 5/16" Square (25,000 lb.) w/Toolbox

Axle Options

(2) 5,200# Electric / Spring (2) 5,200# One Electric / Spring (2) 7,000# Electric / Drop (2) 7,000# Electric / Spring *

(2) 7,000# Electric / Torsion (2) 7,000# One Electric / Spring (2) 7,000# Elec/Hyd Disk / Spring







Lengths LIGHTS 16'- 20'

Standard Features

- 14.000 lb, G,V,W,R.
- 7,000 lb. x 2 G.A.W.R.
- Safety Chains
- I Jack (7,000 lb.)
- 2 Posi-lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- 4 235/80R16 Radial Tires (3,520 lb.)
- Electric Breakaway Kit w/ Charger
- 5' Channel Ramps w/ Holder
- 2x3 Angle Upright
- 2 7/8 Pipe Top Rail
- 5" Channel Tongue & 3" x 5" Angle Frame
- 3" Channel Crossmembers 16" on Center

- 2" Treated Pine Lumber Deck
- · Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

· 25/16" Ball Coupler

- Sealed Wire Harness
- DOT Approved Flushmount Lifetime LED Lights

(2) 8,000# Load Range G Tires Electric / Spring (2) 8,000# Load Range G Tires Electric / Torsion

(2) 7,000# Load Range G I 4ply Tires Electric / Spring

(2) 7,000# Load Range G I 4ply Tires Electric / Torsion

(2) 7,000# Load Range G I 4ply Tires Hydraulic Drum / Spring

(2) 7,000# Load Range G I 4ply Tires Elec/Hyd Disk / Spring

(2) 8,000# Oil Bath Axles w / 235-80 Tires Electric / Spring

(2) 7,000# Oil Bath/Drum Brake / Spring

(2) 7,000# Dexter Electric / Spring

(2) 7,000# Dexter Electric / Torsion

Tail Options

Straight deck w/ 5' Slide-in Ramps *

Color Options

Black Powdercoat * Equipment Yellow Powdercoat Grey Powdercoat Red Powdercoat White Powdercoat

Other Options

I Pair D-Rings Spare Tire Mount Spare Tire and Mount

* denotes a standard feature



AIR RIDE SUSPENSION AVAILABLE

Weights

Length	Axles	Est. Base Weight _†
16'	2 - 7,000	2620 lbs / 1188 kg
18'	2 - 7,000	2830 lbs / 1284 kg
20'	2 - 7,000	3050 lbs / 1383 kg
22'	2 - 7,000	3270 lbs / 1483 kg
24'	2 - 7,000	3480 lbs / 1579 kg



4" Channel Carhauler (C4)





83" x 18' (C4) Pictured

Standard Features

- 7,000 G.V.W.R.
- 7.000 G.A.W.R.
- 2" Ball Coupler
- Safety Chains
- I Pipe Mount Swivel Jack (2,000 lb.)
- 2 Posi-lube Idler Axle (3,500 lb.)
- 4 Leaf Double-eye Spring Suspension
- 4 NEW 15" White Spoke Wheels
- 4 NEW ST205/75R15 Radials (1,820 lb.)
- Stake Pockets
- 9" x 72" Treadplate Removable Alum. Fenders
- 4" Channel Frame & Tongue
- 2 1/2" x 2 1/2" x 3/16" Angle Crossmembers
- 2" Treated Pine Lumber Deck
- 83" Wide Deck

- DOT Approved Flushmount Lights
- Sealed Wire Harness
- · Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight _†
14'	2 - 3,500	1640 lbs / 744 kg
16'	2 - 3,500	1720 lbs / 780 kg
18'	2 - 3,500	1800 lbs / 816 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights

Coupler Options

BP 2"A-Frame *
BP 2 5/16"A-Frame
BP 2"Adjustable
BP 2 5/16"Adjustable
3" Pintle Eye - Channel-mount

Axle Options

- (2) 3,500# One Electric / Spring *
- (2) 3,500# Idler / Spring
- (2) 3,500# Electric / Spring

Tail Options

Straight Deck w/ 5' Slide-in Ramps *
Straight Deck w 4' Fold-up Gate
Straight Deck w/ 4' Heavy Duty Fold-up Gate
2' Dovetail w/ 4' Heavy Duty Fold-up Gate
2' Dovetail w/ 5' Slide-in Ramps

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
Regatta Blue Powdercoat
Tractor Green Powdercoat
White Powdercoat

Other Options

Plate for Winch
Upgrade to 7k Jack
2 D-Rings
Diamond Plate Steel Fenders
LED Lights Upgrade
Rubrail
Spare Tire Mount
Rear Trailer Support Jacks
Spare Tire and Mount
16"oc Crossmembers

^{*} denotes a standard feature



5" Channel Carhauler (C5)





83"x 20'(C5) Pictured

Standard Features

- 7,000 lb. G.V.W.R.
- 3,500 lb. x 2 G.A.W.R.
- 2" Ball Coupler
- Safety Chains
- I Pipe Mount Swivel Jack (5,000 lb.)
- 2 Posi-lube Axles, Idler & Brake (3,500 lb.)
- 4 Leaf Double-eye Spring Suspension
- 4 NEW 15" White Spoke Wheels
- 4 NEW ST205/75R15 Rad. Tires (1,820 lb.)
- Stake Pockets
- Electric Breakaway Kit w/ Charger
- 9" x 72" Treadplate Removable Alum. Fenders
- 5' Channel Ramps w/ Holder
- 5" Channel Frame & Tongue
- 3" Channel Crossmembers 24" on Center

• 2" Treated Pine Lumber Deck

- 83" Wide Deck
- DOT Approved Flushmount Lights
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams TM Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight
14'	2 - 3,500	1740 lbs / 789 kg
16'	2 - 3,500	1850 lbs / 839 kg
18'	2 - 3,500	1970 lbs / 894 kg
20'	2 - 3,500	2080 lbs / 943 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights

Other Options

Cold Weather Wiring Harness (Paris Only)
Upgrade to 225/75 R15 on 3.5k Axles (5.2k Fenders)
10k Jack (Bumper Pull)

Plate for Winch

Upgrade to 235/80 R16 on 52k Axles

Upgrade to 7k Jack

4ft Expanded Metal Sides

Side Mount ATV Ramps (12ft or Longer)

4ft Solid Metal Sides

2 D-Rings

Diamond Plate Fenders

4ft Side Gate (14ft or longer)

Landscape Toolbox (must have 2ft or 4ft Sides)

Open Pit Steel Floor

2" Pipetop Removable Siderails

Rubrail

U8 Side Rail

I I ga Diamond Plate Steel Floor w/ 4 D-Rings

Spare Tire Mount

Rear Trailer Support Jacks

Spare Tire and Mount

16"oc Crossmembers

22" Solid Metal Sides w/ 2" pipe-top

Coupler Options

BP 2" A-Frame *

BP 2 5/16" A-Frame

BP 2" Adjustable

BP 2 5/16" Adjustable

3" Pintle Eye - Channel-mount (14,000 lb.)

Axle Options

- (2) 3,500# One Electric / Spring *
- (2) 3,500# One Electric / Torsion
- (2) 3,500# Electric / Spring
- (2) 3,500# Electric / Torsion
- (2) 3,500# Hyd. Drum w/ Surge Coupler / Spring
- (2) 5,200# One Electric / Spring
- (2) 5,200# One Electric / Torsion
- (2) 5,200# Electric / Spring
- (2) 5,200# Electric / Torsion
- (2) 5,200# Hyd. Drum w/ Surge Coupler / Spring

Tail Options

Straight Deck w/ 5' Slide-in Ramps *

Straight Deck w 4' Fold-up Gate

Straight Deck w/ 2 Fold-up Ramps

Straight Deck w/ 4' Heavy Duty Fold-up Gate

Straight Deck w/ 4' Split Heavy Duty Gate

Straight Deck w/ Rear Slide-in Ramps

2' Dovetail w/ 2 Fold-up Ramps

2' Dovetail w/ 3 Fold-up Ramps

2' Dovetail w/ 4' Heavy Duty Fold-up Gate

2' Dovetail w/ 5' Rear Slide-in Ramps

2' Dovetail w/ 5' Slide-in Ramps

2' Dovetaill w/ Split Heavy Duty Gate

4' Dovetail w/ 2 Fold-up Ramps

4' Dovetail w/ 5' Rear Slide-in Ramps

4' Dovetail w/ 5' Slide-in Ramps

4' Dovetaill w/ Split Heavy Duty Gate

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
Regatta Blue Powdercoat

Tractor Green Powdercoat White Powdercoat

* denotes a standard feature



6" Channel Custom Carhauler (CC)







Lengths LIGHTS 16'- 24'

Standard Features

- 14.000 lb, G,V,W,R.
- 7.000 lb. x 2 G.A.W.R.
- 2 5/16" Ball Adjustable Coupler
- Safety Chains
- I Drop Leg Jack (10,000 lb.)
- 2 Posi-lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- 4 235/80R16 Radial Tires (3,520 lb.)
- Stake Pockets
- Electric Breakaway Kit w/ Charger
- 9" x 72" Treadplate Removable Steel **Fenders**
- 5' Channel Ramps w/ Holder
- Rear Trailer Support Jacks
- Front Toolbox (GN Only)
- 6" Channel Frame & Tongue
- 3" Channel Crossmembers 16" on Center

- 2" Treated Pine Lumber Deck
- 83" Wide Deck (80" w/Torsion or Drop Axles)
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness w/ 7-Way RV Plug
- · Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight;
16'	2 - 7,000	2800 lbs / 1270 kg
18'	2 - 7,000	2950 lbs / 1338 kg
20'	2 - 7,000	3100 lbs / 1406 kg
22'	2 - 7,000	3250 lbs / 1474 kg
24'	2 - 7,000	3400 lbs / 1542 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights



AIR RIDE SUSPENSION AVAILABLE

Other Options

Cold Weather Wiring Harness (7-Way RV) 2nd Jack (Bumper Pull) Plate for Winch 6" Taller GN Riser

Douglas Fir Lumber 9,990 G.V.W.R.

Rubrail

12"oc Crossmembers

I Pair D-Rings

Rough Oak Floor

Drive Over Fenders Receiver Hitch

2 3/8" Removable Pipetop on Siderails

Diamond Plate Running Boards

Steel Floor & 4 D-Rings

Front Toolbox (Bumper Pull)

102" Deck Width

Mount Only for Spare Tire

Spare Tire and Mount (Bumper Pull)

Deck on the Neck (GN Only)

Rear Trailer Support Jacks

Winch 12VDC (12,000 lb.) Incl. Front Toolbox

2-speed Jacks (12,000 lb.)

HD Trailer 2x Jacks (25k lb.) No Frt T/box GN Only

Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) * Rigid mount 2-5/16 (25,000 lb.)

GN 2 5/16" Round (30,000 lb.) w/Toolbox

GN Load-Leveling 2 5/16" Square (30,000 lb.) & Tbx

3" Pintle Eye - Channel-mount (20,000 lb.) GN 2 5/16" Square (30,000 lb.) w/Toolbox

GN 2 5/16" Round (25,000 lb.) w/Toolbox

GN 2 5/16" Square (25,000 lb.) w/Toolbox

HD 2 5/16" Adjustable Channel Mount 3 Bolt Coupler

Axle Options

- (2) 5.200# Electric / Spring
- (2) 5,200# Electric / Torsion
- (2) 5,200# Hydraulic Drum / Spring
- (2) 7,000# Electric / Drop
- (2) 7,000# Electric / Spring *
- (2) 7,000# Electric / Torsion
- (2) 7,000# Hydraulic Drum / Spring
- (2) 7,000# Elec/Hyd Disk / Spring
- (2) 7,000# Oil Bath/Drum Brake / Spring
- (3) 7,000# Electric / Spring
- (3) 7,000# Electric / Torsion
- (3) 7,000# Elec/Hyd Disk / Spring
- (2) 8,000# Oil Bath Axles w / 235-80 Tires Electric / Spring
- (2) 8,000# Load Range G Tires Electric / Spring
- (2) 8,000# Load Range G Tires Electric / Torsion
- (3) 8,000# Load Range G Tires Electric / Spring

Tail Options

Straight deck w/ 5' Slide-in Ramps * Straight Deck w/ 4' Heavy Duty Fold-up Gate

Straight deck w/ 5' Fold-up Ramps

Straight deck w/ HD Fold-up Ramps

Straight Deck w/ Rear Slide-in Ramps

2' Dovetail w/ 3 5' Fold-up Ramps

2' Dovetail w/ 5' Double Hinge Fold-up Ramps

2' Dovetail w/ 5' Fold-up Ramps

2' Dovetail w/ 5' Slide-in Ramps

2' Dovetail w/ 5' with Rear Slide-in Ramps

2' Dovetail w/ HD Fold-up Ramps

2' Dovetaill w/ Split Heavy Duty Gate

2" Dovetail w/ 4' Heavy Duty Fold-up Gate

4' Dovetail w/ 5' Double Hinge Fold-up Ramps

4' Dovetail w/ 5' Fold-up Ramps

4' Dovetail w/ 5' Slide-in Ramps

4' Dovetail w/ 5' with Rear Slide-in Ramps

4' Dovetail w/ HD Fold-up Ramps

Color Options

Black Powdercoat *

Equipment Yellow Powdercoat

Grey Powdercoat

Red Powdercoat

White Powdercoat



8" Channel Carhauler (C8)









Lengths 20' - 40'

Standard Features

- 14.000 lb, G,V,W,R.
- 7.000 lb. x 2 G.A.W.R.
- 2 5/16" Ball A-Frame Coupler
- Safety Chains
- I Drop Leg Jack (10,000 lb.)
- 2 Posi-lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- 4 235/80R16 Radial Tires (3,520 lb.)

Stake Pockets

Electric Breakaway Kit w/ Charger

9" x 72" Treadplate Removable Steel Fenders

5' Channel Ramps w/ Holder

Rear Trailer Support Stands

Front Toolbox (GN Only)

- 2" Treated Pine Lumber Deck
- 83" Wide Deck (80" w/ Torsion Axles)
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness
- · Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Weights

Length	Axles	Est. Base Weight _†
20'	2 - 7,000	3340 lbs / 1515 kg
22'	2 - 7,000	3530 lbs / 1601 kg
24'	2 - 7,000	3720 lbs / 1687 kg
26'	2 - 7,000	3910 lbs / 1774 kg
28'	2 - 7,000	4100 lbs / 1860 kg
30'	2 - 7,000	4300 lbs / 1950 kg
32'	2 - 7,000	4490 lbs / 2037 kg
34'	2 - 7,000	4680 lbs / 2123 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights



AIR RIDE SUSPENSION AVAILABLE

Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) *
Rigid mount 2-5/16 (25,000 lb.)
GN 2 5/16" Round (30,000 lb.)

GN Load-Leveling 2 5/16" Square (30,000 lb.)
3" Pintle Eye - Channel-mount (21,000 lb.)

GN 2 5/16" Square (30,000 lb.)

GN 2 5/16" Round (25,000 lb.)

GN 2 5/16" Square (25,000 lb.)

Axle Options

(2) 7,000# Elec / Drop

(2) 7,000# Elec / Spring *

(2) 7,000# Elec / Torsion**

(2) 7,000# Elec/Hyd Disk / Spring

(3) 7,000# Elec / Spring

(3) 7,000# Elec / Torsion**

(3) 7,000# Elec/Hyd Disk / Spring

(2) 7,000# 14Ply Tires Elec / Spring

(2) 7,000# 14Ply Tires Elec / Torsion**

(2) 7,000# 14Ply Tires Elec/Hyd Disk / Spring

(3) 7,000# 14Ply Tires Elec / Spring

(3) 7,000# 14Ply Tires Elec / Torsion**

(3) 7,000# 14Ply Tires Elec/Hyd Disk / Spring

(2) 8,000# 14Ply Tires Elec / Spring**

(3) 8,000# 14Ply Tires Elec / Spring**

** (note only 80" between fenders on CH)

Tail Options

Straight deck w/ 5' Slide-in Ramps *
2' Dovetail w/ 5' Slide-in Ramps
2' Dovetail w/ 5' Fold-up Ramps
Straight deck w/ 5' Fold-up Ramp

Color Options

Black Powdercoat *
Equipment Yellow Powdercoat
Grey Powdercoat
Red Powdercoat
White Powdercoat

Other Options

2nd Jack (Bumper Pull) Plate for Winch 6" Taller GN Riser 9,990 G.V.W.R. Rubrail 12"oc Crossmembers I Pair D-Rings Oak Floor Drive Over Fenders Hydraulic Jacks (12,000 lb.) Receiver Hitch LED Light Package 2 3/8" Removable Pipetop on Siderails Diamond Plate Running Boards Steel Floor & 4 D-Rings 102" Deck Width Mount Only for Spare Tire Spare Tire and Mount (Bumper Pull) Deck on the Neck (GN Only) Winch 12VDC (12,000 lb.) 2-speed Jacks (12,000 lb.) 2-speed Jacks, (12,000 lb.) No Front Toolbox

* denotes a standard feature



Light Duty Deckover 5" Channel (L5)



Standard Features

- 7,000 lb, G,V,W,R.
- 3,500 lb. x 2 G.A.W.R.
- 2 5/16" Adjustable Ball Coupler
- Safety Chains
- I Drop Leg Jack (7,000 lb.)
- 2 Posi-lube Brake Axles (3,500 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 15" White Spoke Wheels
- 4 205/75R15 Radial Tires (1,800 lb.)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape

- 6' Slide in Ramps w/ Holders
- 5" Channel Tongue
- 5" Channel Frame Main Frame
- 3x2" Angle Channel Crossmembers 16" on Center 2" Treated Pine Lumber Deck
- 101"Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness
- · Sand Blasted, Acid Washed, Powder Coated



Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) * 3" Pintle Eye - Channel-mount (21,000 lb

Axle Options

(2) 3,500# Electric / Spring *

Tail Options

Straight Deck w/ 6'6" Slide-in Ramps *

Other Options

I Pair D-Rings Spare Tire and Mount (Bumper Pull) V Shape Front Deck

* denotes a standard feature

Weights

Length	Axles	Est. Base Weight
16'	2 - 3,500	2500 lbs / 1134 kg
18'	2 - 3,500	2660 lbs / 1207 kg
20'	2 - 3,500	2800 lbs / 1270 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights



Medium Duty Deckover 6" Channel (L6)



Standard Features

- 9,990 lb, G,V,W,R.
- 5,200 lb. x 2 G.A.W.R.
- 2 5/16" Adjustable Ball Coupler
- Safety Chains
- I Drop Leg Jack (7,000 lb.)
- 2 Posi-lube Brake Axles (5,200 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 15" White Spoke Wheels
- 4 225/75R15 Radial Tires
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 6' Slide in Ramps w/ Holders

- 6" Channel Tongue
- 6" Channel Frame Main Frame
- 3x2" Angle Channel Crossmembers 16" on Center
- 2" Treated Pine Lumber Deck
- 101" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated



Coupler Options

BP 2 5/16" Adjustable (14,000 lb.) * 3" Pintle Eye - Channel-mount (21,000 lb

Axle Options

(2) 5,200# Electric / Spring *

Tail Options

Straight Deck w/ 6'6" Slide-in Ramps *

Other Options

I Pair D-Rings
Share Tire and Mou

Spare Tire and Mount (Bumper Pull) V Shape Front Deck

* denotes a standard feature

Weights

Leng	th A xle	es Est. l	Base Weight _†
16'	2 - 5,2	200 2820	lbs / 1279 kg
18'	2 - 5,2	200 2980	lbs / 1352 kg
20'	2 - 5,2	200 3020	lbs / 1370 kg

Coupler Options



Bumper Pull

Tail Options



3" Pintle Eye



8" I-Beam Gooseneck (CC)



12" I-Beam Gooseneck (C8) 24+ ft only

Color Options



Black Powder Coat



Eq. Yellow Powder Coat



Grey Powder Coat



White Powder Coat



Red Powder

Coat

(actual color may vary)

Straight deck w/5' Slide-in Ramps



2' Dovetail w/ 5' Slide-in Ramps



Straight deck w/ 5' Fold-up Ramps



2' Dovetail w/ 5' Fold-up Ramps

Other Options



Receiver Hitch



Rubrail



Winch 12VDC (12,000 lb.)




Deck on the Neck (GN Only)



1 Pair D-Rings



Rough Oak Floor



Steel Floor & 4 D-Rings



Spare Tire Mount



Diamond Plate Running **Boards**



2 3/8" Pipetop Removable Siderails (CC, C8)



TrailerFlex Air Ride Suspension



2' Dovetail w/ HD Fold-up Ramps



PJ TRAILERS

- #1 Professional Grade Open Trailer Manufacturer
- Broad Line of Dumps, Flatdecks, Utilities, Tilts & Equipment Trailers
- Over 300 Independent PJ Trailers Dealer Locations in the US & Canada