

Hydraulic Jacks

Norco Hydraulic Bottle Jacks

Fifty-percent safety overload factor. Easier to repair than threaded jack designs. Fewer working parts, internally machined oil passages, extremely smooth bearing surfaces and close tolerances ensure longer life, fewer breakdowns. No-leak "Uniweld" construction. Carrying handle included.



- 410191** 12 Ton Standard; 4/Ctn.
- 410190** 12 Ton Shorty; 4/Ctn.
- 410192** 20 Ton; 4/Ctn.
- 410194** Repair Kit f/20 Ton: 76520, 76820, 2103, 9672, 1120, 920, 5692
- 410196** Repair Kit f/20 Ton: 76520, 76820 (2-9/16" plunger)
- 410188** Repair Kit f/12 Ton: 76412, 76512, 2102, 9306, 91012, 1112, 912 & 5691 (3" plunger)
- 410189** Repair Kit f/12 Ton (2-9/16" plunger)
- 410193** Oil Filler Plug; 25/Ctn.

Air Hydraulic Jacks




Equipped with U.S. Patented air motor kit for quick and easy lifting. Quick connector hose provides easy removal of air hose. Uses standard shop air. Minimum height: 9.5" H; maximum: 18-5/8" H.

- 410050** 12 Ton; 26 lbs.
- 410051** 20 Ton; 35.2 lbs.

Latch Replacement Kit

Fits 2-5/16" ball, A-frame only. Includes 1 latch assembly, 1 bolt and 1 hex nut.



410149


Top-Wind Jack

Triangular mounting bracket provides for easy bolt-on or weld-on mounting through A-frame mounted couplers. Casters quickly install and lock in key slot on jack ram. 5000 lb. capacity. Comes with bottom plate.



410125

Eaz-Lift Sway Control



Minimizes sway caused by passing trucks and sudden wind gusts. Double friction disc brake principle provides constant sway abatement. Attaches with easy socket and spring clip connectors. Removes for easy storage.

503606

Atwood Hitch Ball

Machine finish. 2-5/16" x 1-1/4", 40,000 capacity.


410210



Master Trailer Locks

Covers coupler opening with powerful housing. Quality pin tumbler locking mechanism. Weather-resistant finish.

- 411221** F/2" & 2-5/8" Marvel; 6/Ctn.
- 411222** F/2" & 2-5/8" Atwood; 18/Ctn.



Towing Safety Flags

Red Flag & Clip Kit

Meets regulations. Two bright red ravel-proof nylon tricot flags and two plastic flag clips. Clear-bagged.

- 341907** 18" x 18"
- 341908** 24" x 24"




Red Flag



Red tricot nylon, plain edges. High level of reflectancy. In packs of 6. 240/Ctn.

- 341911** 18" x 18"
- 341912** 24" x 24"

Plastic Clips




- 341909** Each
- 341904** Bag of 25; 40/Ctn.



Flag & Staff

Nylon tricot flag mounted on heavy-duty 36" staff. Ideal for front of tow trucks where required. 24" x 24".

341905



Flag Holder

Galvanized steel, bolt-on mount. Thumb screw holds secure. All hardware included. 24/Ctn.

341906

18" Shock Cord



Strong, durable straps of high grade rubber for attaching flexible signs, banners, etc. Versatile; many uses.

342101 100/Ctn.

Tarp Straps




Trucker's hard rubber snubbers with iodized S-hooks for superior resiliency and long life.

- 342102** 15"; 50/Ctn.
- 342103** 22"; 50/Ctn.
- 342104** 31"; 50/Ctn.



Quickie Tie Down

NEW!



Hook it up, pull it tight, and zip! It's done! The quickest, toughest, safest tie-down on the market.

- Lightweight yet strong, heavy duty 3/8"
- Self-locking, quick release
- Cinches tightly in place without knots or buckles
- All parts are corrosive-resistant
- Easy-release trigger is recessed to prevent accidental triggering
- Rubber-coated hooks protect vehicles and prevent slipping
- Safer than bungees with no slap-back or snapping
- 8' length of rope



342107

Displays available

Transport Lights

Strobe Beacons

Versatile & powerful with 5.5" amber lens and computer designed optics. Universal anodized aluminum mounting base. Accommodates surface, pipe or magnetic mount options. Double flash.



- 340850** 5.5" High
- 340851** 4" High, Magnetic Mount
- 340852** Replacement Flash Tube

Low Profile Light Bars

Four Halogen rotator model with two diamond mirrors. Redesigned reflector with pre-focused halogen bulb for more light intensity. 110 RPM per rotating module. Relampable 50 watt equivalent intensity (35 watt halogen) bi-pin bulb. Shatter-resistant polycarbonate outer lens, amber warning color.

- 340855** 48" Wide



Amber Minibar



Shatter-resistant polycarbonate outer dome, non-corroding molded nylon base, low current consumption, easy to service with modular parts. 55 watt Halogen light, 8 amp draw. 16" x 4.75".

- 340856** Permanent Mount
- 340857** Magnetic Mount, Adapter & Cord
- 340858** Replacement Outer Dome
- 340859** Replacement Bulb

Prices and Specifications Subject to Change without Notice



Unibeacon™ Sealed Beam Revolving Warning Lights

Features 12-volt halogen and incandescent sealed beam lamps with computer-engineered light patterns, 5" single, two and four lamps with 35 watts and 33,000 candlepower each, 10' cord that plugs into any standard vehicle cigarette lighter receptacle. The single sealed beam features a chrome-plated base with a LEXAN® dome. All other lights feature stainless steel bases with LEXAN® domes. Unibeacon™ lights feature a continuous-duty enclosed motor with direct drive and a protective slip clutch.



Single Beam

90 flashes per minute, glare shield for dash mount included. 6.1" W x 7.0" H

- 340801** Permanent Mount Light
- 340802** Magnet Mount Light
- 340183** Amber Replacement Lens
- 340180** Replacement Sealed Beam

Two Beam

100 flashes per minute. 8.5" W x 8.5" H

- 340200** Permanent Mount Light
- 340182** Amber Replacement Lens
- 340180** Replacement Sealed Beam



Four Beam

100 flashes per minute with longer dwell per flash. 11" W x 9.8" H.

- 340701** Permanent Mount Light
- 340181** Amber Replacement Lens
- 340180** Replacement Sealed Beam



Safety Signs

Vinyl Double-Sided Sign



Features a strong 1/4" poly rope sewn the entire length; all the stress goes to the rope, not on the sign, so there are no grommets to tear out. 12" high letters are screen printed black on interstate yellow. "Oversize Load" on one side & "Wide Load" on the other.

342016 20" x 84"; 25/Ctn.

Metal Double-Sided Sign



Light-weight metal alloy sign. Baked-on enamel finish, scratch resistant. Will not fade, crack, peel or rust. Custom-designed fold for easy storage. Black on interstate yellow. 12" letter height and 2" letter stroke.

342009 15" x 6'

342010 18" x 7' (PA Approved)

Oversize Load (Ohio DOT)

Vinyl mesh open weave meets Ohio DOT regulations. 12" x 60" with 8" letters.

342003



Poly-Coated Fabric Highway Signs

Long lasting, durable and weatherproof, reinforced metal grommets, double stitched seams and Tyvek corners for extra strength. Attaches easily with shock cords. Black letters on interstate yellow background.



Cloth sleeve numbered 10, 12, 14 and 16 enables sign to address every Arkansas sign requirement. Letter height 12", stroke 2".

342001 Over Size XX Load, 18" x 7'; 25/Ctn.



342002 Over Size Load; 18" x 8', Michigan Approved; 25/Ctn.



342005 Danger - Wide Load Ahead, 18" x 4'; 25/Ctn.




342007 Danger - Wide Load Follows, 18" x 4'; 25/Ctn.

20-Minute Flare with Spike



340806 72/Ctn.



Safety Triangles

Triangle reflector kit with 3 triangles. D.O.T. approved. American-made.

340804 6/Ctn.

Kidde BC Fire Extinguishers

- ⌘ Dry chemical agent: Sodium Bicarbonate
- ⌘ Inhibits reflash
- ⌘ Easy to clean up
- ⌘ Non-corrosive to metal

340501 5:1 BC, 2 lbs.

Recommended f/Homes

340507 10:1 BC, 2.75 lbs.

Recommended f/Vehicles

All Kidde fire extinguishers offer:

- ⌘ Professional gauges
- ⌘ Fast, reliable pressure check
- ⌘ Seamless aluminum resists corrosion



Kidde ABC Fire Extinguishers

Non-toxic, tri-class dry chemical agent (monoammonium phosphate) fights flammable liquids and electric fires as well as wood, paper and cloth fires.

340508 1A10BC, 2.20 lbs.

Recommended f/Commercial Use

340509 1A10BC, 5 lbs.

Recommended f/Commercial Use

Traction Mats



Get vehicles and equipment over lawns, through mud and across soft terrain while saving labor, bog-down time, towing charges and ground restoration fees—perfect for set-ups.

- ◆ 1/2" 100% recycled polyethylene plastic
- ◆ Virtually indestructible
- ◆ Double-sided, skid and slip resistant
- ◆ Low cost alternative to fiberglass mats
- ◆ Easily portable
- ◆ Maintenance free

265301 2' x 4'

265302 2' x 6'

265303 2' x 8'

265304 4' x 8'

FIREX

Smoke Alarm



120VAC, 60 HZ, bipolar dual ionization sensing chamber, bug resistant with louder horn to meet U.L. Standard 217. Interconnect up to 6 units. LED blinks once per minute, auto reset and 5-yr. limited warranty. Quick connect wiring harness.

141302 Electric, 4-7/8" dia. x 1-3/16" H

141303 Battery* 4" dia. x 1-1/8" H

* Not Included

Smoke Alarm with Battery Back-up


Direct wire 120V AC, 60HZ with 9 volt battery back-up in case of power failure (not included). Front loading battery door for easy changes, unique PowerLink Tab allows alarm to be shipped with battery already installed. False Alarm Control quiets unwanted alarms for up to 15 minutes. Factory-sealed housing, attractive low profile design. 85 decibel horn, test switch, dual purpose LED indicator: constant green confirms AC power is present and the flashing red displays battery/ alarm status. Interconnects with other Firex smoke and heat alarms. U.L. Standard 217.

141305 4-7/8" dia. x 1-3/8" H

Personal Safety

Adjustable Support Belt


- ⌘ Prevents Injury
- ⌘ Reduces Workers Comp Claims
- ⌘ Reduces Discomfort



Adjustable-size support belt with built-in elastic suspenders gives comfortable back support for everyday use, to reduce or prevent lower back pain or strain. Fully-enclosed spring steel stays for flexible, contoured support and easy-adjust elastic outer panels for added lower back support.

345006 32" to 38" Waist
345007 38" to 47" Waist


All Leather Work Gloves



- ⌘ Front, back & leather cuff
- ⌘ Double leather palm
- ⌘ Double stitched
- ⌘ Sold as pairs with hang-up display cards

345016


Leather Palm Work Gloves



- ⌘ Full leather palm with leather knuckle band & fingers
- ⌘ Split leather cowhide
- ⌘ Double stitched
- ⌘ Heavy canvas gauntlet cuff for added protection
- ⌘ Sold as pairs with hang-up display cards

345015

Rubber Knee Pads



Quick and easy on/off with 2" wide single elastic velcro straps.

345010

First Aid Kit

- ⌘ First aid booklet
- ⌘ 2 Knuckle Cover Bandages
- ⌘ 6 antiseptic towels
- ⌘ Instant ice pack
- ⌘ 3 gauze bandages 3" x 3"
- ⌘ 8 bandages 3/4" x 3"
- ⌘ 2 burn/infection ointments
- ⌘ 1 roll of adhesive tape
- ⌘ Carrying pouch




Convenient 25-pc. first aid kit fits inside glove compartment or stores in trunk.

340808 6/Ctn.

Break & Axle Parts

Shur-Set III™ Breakaway Kit



Mounts on jackpost or A-frame. Quick, easy, one-bolt installation—no cutting or drilling needed. Rust-proof polyethylene plastic case protects battery and charger from elements and corrosion. Meets or exceeds DOT specifications regarding breakaway/holding requirements. Complete kit includes: battery case with mounting bracket; 12V sealed, rechargeable battery; and nylon breakaway switch. *Battery charger sold separately.*

340105 Breakaway Kit; 10/Ctn.

340103 Switch Only; 20/Ctn.


Breakaway Switch



Sets trailer brakes in case of accidental trailer breakaway. Trailer brakes are applied automatically. Reinforced nylon case. Rust and corrosion free to assure long life. Silver contact points remain corrosion free for positive contact. Nylon pull-pin can't freeze up, assuring positive activation.

340103

Battery Charger




12 volt. Fits securely in battery case with battery. Compatible with all automotive electrical systems. Automatic shutoff prevents overcharging. Designed to provide exact amperage needed to sealed, wet cell battery.

340106 Battery Charger

171910 12 Volt Battery

Lug Bolt



1/2" dia. and 2-1/4" long. For use with cast hubs that are drilled and tapped. 1/2 - 13 threads.


154109

1/2" dia. and 1-7/8" long. For use with cast hubs that are drilled and tapped. 1/2 - 20 threads.

153108

Universal Rim Clamp


Heavy-cast. Universal, will fit most mobile home axles, fits axles using either lug bolts or lug studs. Sometimes referred to as wedges.



157125

Lug Nut


Plated steel, 1/2" with 20 threads per inch. Heavy hex.



157130


Lug Stud

Plated. 1/2" dia., 2" long, 1/2 - 20 threads. Fits only Continental axles with formed steel hubs.



157124

Wheel Bolt



1/2-20

150316

Tandem Axle Parts

Four-Leaf Spring




3000lb. cap. 25-1/4" c/c eyes (unloaded) & 1-3/4" wide at eyes. Use 1/2" or 9/16" dia. shackle bolts. For best results, replace in pairs.

156920

Spring Clamp Plate

Heavy 1/4" thick steel for use with up to 1/2" dia. U-bolts. Holes are spaced for 3-5/8" wide. U-bolts 2-3/8" apart.




156950


Shackle Link

1/4" thick steel, 1-1/4" wide. Use with 1/2" or 9/16" dia. shackle bolt to connect to equalizer or to spring hanger. Hole centers: 2-1/4".

157162




Spring Hanger



1/4" thick heavy steel, for use w/1-3/4" wide spring. Hanger is 3" long, drop 2-1/4". For use with 9/16" or 1/2" dia. shackle bolt.

157161

Steel Equalizer




Heavy 1/4" steel with new strong design to distribute load, preventing undue stress to axles or mobile home frame. Uses 1/2" or 9/16" dia. shackle bolts.

157164

Rugged cast. Use 1/2" or 9/16" dia. shackle bolts.

A: 6-1/16"
B: 4-1/16"
D: 1-3/4"


157170



Spring Mounting Pad

Heavy steel, fits 3" OD axle tube. Must be welded to axle tube, one for each spring. 1-15/16" wide, 4-1/2" long.

156955



Shackle Bolt & Nut



Steel, 9/16" dia. and 3" long. Hex lock nut included.

157166

1/4" thick heavy steel, for use w/1-3/4" wide spring. Hanger is 1-3/4" long, drop 1-1/8". Use only at shackle end of single axle suspensions.

157168


1/4" thick heavy steel, for use w/1-3/4" wide spring. Hanger is 13" long, drop 3-1/4". Use with 9/16" or 1/2" dia. x 3" shackle bolt.

157160

U-Bolt w/Nut

1/2" dia. for mounting mono-leaf spring to 3" dia. axle tube. Self-locking nuts included.

156915



1/2" dia. for mounting four-leaf spring to 3" dia. axle tube. Self-locking nuts included.

156925

Bearing Cup

157182 L 68111



Bearing Cone

L 68149, high grade alloy steel.

157184



LM 67048, high grade alloy steel.

157188

Grease Seal



ABS plastic, long-wearing. 2-7/16" OD, 1.840" ID lip seal. (Refer to old seal dimension before ordering).

157174

ABS plastic, long-wearing. 3-3/8" OD, 2.245" ID lip seal. (Refer to old seal dimension before ordering).

157176

Dust Cap



Universal plated, will fit most axles, keeps grease in and dirt out to protect bearings.

156900

Spindle Nut

Universal assembly comes with 1" dia. washer, 1/8" x 1-1/2" long cotter pin, and 1" dia. slotted hex nut.

157172