

LOAD/INFLATION INFORMATION

LOAD/INFLATION INFORMATION FOR RV ST METRIC TIRES TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating (MPH)	Inflation Pressure - PSI										
		15	20	25	30	35	40	45	50	55	60	65
ST175/80R13	65	670	795	905	1000	1100(B)	1190	1270	1360(C)			
ST185/80R13	65	740	870	990	1100	1200(B)	1300	1400	1480(C)			
ST205/75R14	65	860	1030	1170	1300	1430(B)	1530	1640	1760(C)			
ST215/75R14	65	953	1110	1270	1410	1520(B)	1660	1790	1870(C)			
ST205/75R15	65	905	1070	1220	1360	1480(B)	1610	1720	1820(C)			
ST225/75R15	65	1060	1260	1430	1600	1760	1880	2020	2150(C)	2270	2380	2540(D)
ST235/80R16	65			1720	1920	2090	2270	2430	2600	2730	2870	3000(D)

LOAD/INFLATION INFORMATION FOR RV TIRES TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Single (S) Dual (D)	Inflation Pressure - PSI															
		35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110
LT215/75R15	S	1345	1475	1600	1765(C)	1845	1960	2095(D)									
	D	1225	1340	1455	1610(C)	1680	1785	1930(D)									
LT235/75R15	S	1530	1680	1825	1895(C)	2100	2230	2335(D)									
	D	1390	1530	1660	1820(C)	1910	2030	2150(D)									
LT225/75R16	S	1500	1650	1790	1940(C)	2060	2190	2335(D)	2440	2560	2680(E)						
	D	1365	1500	1630	1765(C)	1875	1995	2150(D)	2200	2330	2470(E)						
LT245/75R16	S	1700	1865	2030	2205(C)	2335	2480	2623(D)	2765	2900	3042(E)						
	D	1545	1695	1845	2006(C)	2125	2255	2381(D)	2515	2640	2778(E)						
LT215/85R16	S	1495	1640	1785	1940(C)	2050	2180	2335(D)	2430	2550	2680(E)						
	D	1360	1490	1625	1765(C)	1865	1985	2150(D)	2210	2320	2470(E)						
LT235/85R16	S	1700	1870	2030	2205	2335	2485	2623(D)	2765	2905	3042(E)	3170	3300	3415	3550	3675	3750(G)
	D	1545	1700	1845	2006	2125	2260	2381(D)	2515	2645	2778(E)	2885	3005	3085	3230	3345	3415(G)
7.50R16LT	S	1620	1770	1930	2040(C)	2190	2310	2470(D)	2560	2670	2755(E)						
	D	1430	1565	1690	1820(C)	1930	2040	2150(D)	2245	2345	2470(E)						
8.75R16.5	S						2240	2405	2470	2570	2680(E)						
	D						1970	2095	2175	2260	2405(E)						

*Industry standards for load & inflation are in the process of being revised. These tables are current as of 01/01/05. For the most current information, please visit the RV Tire section of Goodyear's Web site at www.goodyear.com/rv.

LOAD/INFLATION INFORMATION

LOAD/INFLATION INFORMATION FOR RV TIRES

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) TRAILER DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating (MPH)	Single (S) Dual (D)	Inflation Pressure - PSI											
			70	75	80	85	90	95	100	105	110	115	120	125
215/17.5	75	S					3695	3860	4020	4180	4340	4495	4650	4806(H)
		D					3490	3645	3800	3950	4100	4245	4395	4540(H)

LOAD/INFLATION INFORMATION FOR RV TIRES

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL-POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating (MPH)	Single (S) Dual (D)	Inflation Pressure - PSI											
			65	70	75	80	85	90	95	100	105	110	115	120
8R19.5	75	S	2410	2540	2680	2835	2955	3075	3195	3305	3415	3525(F)		
		D	2350	2460	2610	2755	2865	2975	3085	3195	3305	3415	3415(F)	
225/70R19.5	75	S		2895	3040	3195	3315	3450	3640(F)	3715	3845	3970(G)		
		D		2720	2860	3000	3115	3245	3415(F)	3490	3615	3750(G)		
245/70R19.5	75	S		3640	3740	3890	4080(F)	4190	4335	4540(G)				
		D		3415	3515	3655	3970(F)	4115	4265	4410(G)				
†245/70R19.5	75	S				3640	3740	3890	4080(F)	4190	4335	4540(G)		
		D				3415	3515	3655	3970(F)	4115	4265	4410(G)		
265/70R19.5	75	S				3970	4180	4355	4540	4685	4850	5070	5170	5355(G)
		D				3750	3930	4095	4300	4405	4560	4805	4860	5070(G)

†Tires produced after 2/28/06.

Tire Size	Max Speed Rating (MPH)	Single (S) Dual (D)	Inflation Pressure - PSI											
			70	75	80	85	90	95	100	105	110	115	120	
9R22.5	75	S	3370	3560	3730	3890	4080	4235	4390	4540(F)				
		D	3270	3410	3550	3690	3860	4005	4150	4300(F)				
10R22.5	65	S	4080	4280	4480	4675	4850	5025	5205(F)	5360	5515	5675(G)		
		D	3860	4045	4230	4410	4585	4760	4940(F)	5075	5210	5355(G)		
11R22.5	75	S	4530	4770	4990	5220	5510	5730	5950	6175(G)	6320	6465	6610(H)	
		D	4380	4580	4760	4950	5205	5415	5625	5840(G)	5895	5950	6005(H)	
12R22.5	75	S	4940	5200	5450	5690	6005	6205	6405	6610	6870	7130	7390(H)	
		D	4780	4990	5190	5390	5675	5785	5895	6005	6265	6525	6780(H)	
245/75R22.5	75	S	3470	3645	3860	3980	4140	4300	4455	4610	4675(G)			
		D	3260	3425	3640	3740	3890	4080	4190	4335	4410(G)			

LOAD/INFLATION INFORMATION

LOAD/INFLATION INFORMATION FOR RV TIRES

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL-POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating (MPH)	Single (S) Dual (D)	Inflation Pressure - PSI											
			70	75	80	85	90	95	100	105	110	115	120	125
255/70R22.5	75	S			4190	4370	4550	4675	4895	5065	5205	5400	5510(H)	
		D			3970	4110	4275	4410	4455	4610	4675	4915	5070(H)	
265/75R22.5	75	S	3875	4070	4255	4440	4620	4800	4975	5150	5205(G)			
		D	3870	4040	4205	4370	4525	4685	4805(G)					
275/70R22.5	75	S				5170	5400	5630	5850	6070	6290	6510	6730	6940(H)
		D				4770	4980	5180	5390	5590	5800	6000	6200	6395(H)
275/70R22.5 (G159)	75	S				4885	5080	5305	5530	5750	5965	6185	6400	6610(H)
		D				4535	4750	4960	5165	5370	5575	5775	5975	6175(H)
275/80R22.5	75	S					5500	5745	5985	6225	6460	6700	6930	7160(H)
		D					5080	5305	5530	5750	5965	6185	6400	6610(H)

Tire Size	Max Speed Rating (MPH)	Single (S) Dual (D)	Inflation Pressure - PSI											
			75	80	85	90	95	100	105	110	115	120	125	130
295/75R22.5	75	S	4725	4940	5155	5370	5510	5780	5980	6175(G)	6370	6610(H)		
		D	4690	4885	5070	5260	5440	5675(G)	5800	6005(H)				
295/80R22.5	75	S		5480	5750	6020	6285	6550	6810	7070	7320	7580	7830(H)	
		D		4855	5100	5335	5570	5805	6035	6265	6490	6720	6940(H)	
315/80R22.5	75	S			6415	6670	6940	7190	7440	7610	7920	8270	8680	9090(L)
		D			5840	6070	6395	6540	6770	6940	7210	7610	7940	8270(L)
11R24.5	75	S		5310	5550	5840	6095	6350	6610(G)	6790	6970	7160(H)		
		D		5070	5260	5510	5675	5840	6005(G)	6205	6405	6610(H)		

*Industry standards for load & inflation are in the process of being revised. These tables are current as of 01/01/05. For the most current information, please visit the RV Tire section of Goodyear's Web site at www.goodyear.com/rv.